



# SERENA

# SERENA DASHBOARD

Synonyms Reference

Serena Proprietary and Confidential Information

---

Copyright © 2011–2012 Serena Software, Inc. All rights reserved.

This document, as well as the software described in it, is furnished under license and may be used or copied only in accordance with the terms of such license. Except as permitted by such license, no part of this publication may be reproduced, photocopied, stored in a retrieval system, or transmitted, in any form or by any means, electronic, mechanical, recording, or otherwise, without the prior written permission of Serena. Any reproduction of such software product user documentation, regardless of whether the documentation is reproduced in whole or in part, must be accompanied by this copyright statement in its entirety, without modification. This document contains proprietary and confidential information, and no reproduction or dissemination of any information contained herein is allowed without the express permission of Serena Software.

The content of this document is furnished for informational use only, is subject to change without notice, and should not be construed as a commitment by Serena. Serena assumes no responsibility or liability for any errors or inaccuracies that may appear in this document.

## **Trademarks**

Serena, TeamTrack, StarTool, PVCS, Collage, Comparex, Dimensions, Serena Dimensions, Mashup Composer, Mashup Exchange, Prototype Composer, Mariner, and ChangeMan are registered trademarks of Serena Software, Inc. The Serena logo, Version Manager, Meritage, and Mover are trademarks of Serena Software, Inc. All other products or company names are used for identification purposes only, and may be trademarks of their respective owners.

Telelogic and DOORS are either registered trademarks or trademarks of Telelogic AB in the United States and/or other countries. Rational and IBM are either registered trademarks or trademarks of IBM in the United States and/or other countries. Eclipse is a trademark of the Eclipse Foundation in the United States and/or other countries. All other products or company names are used for identification purposes only, and may be trademarks of their respective owners.

## **U.S. Government Rights**

Any Software product acquired by Licensee under this Agreement for or on behalf of the U.S. Government, its agencies and instrumentalities is "commercial software" as defined by the FAR. Use, duplication, and disclosure by the U.S. Government is subject to the restrictions set forth in the license under which the Software was acquired. The manufacturer is Serena Software, Inc., 1850 Gateway Drive, 4th Floor, San Mateo, California, 94404-4061.

Part number: Product version: 4.0

Publication date: 2012-10-25

# Table of Contents

- Table Reference ..... 1
- Dashboard\_Schema\_Intro ..... 6
  - Overview ..... 6
  - Understanding Synonyms..... 6
  - Displaying Serena Dashboard Synonyms ..... 7
  - Using This Content ..... 9
- Dashboard\_Schema\_RLM ..... 9
  - Introduction ..... 9
    - Data Sources for Release Manager Metrics ..... 9
    - Representing Data with Synonyms..... 9
    - Using This Content ..... 9
  - Synonym Overview ..... 9
  - Release Trains ..... 10
    - Out of the Box Usage ..... 10
    - Object Reference..... 10
  - Release Packages ..... 11
    - Example Out of the Box Usage ..... 11
    - Object Reference..... 11
  - System Data ..... 12
    - Object Reference..... 12
  - Deployment Tasks ..... 14
    - Out of the Box Usage ..... 14
    - Object Reference..... 14
  - Releases ..... 15
    - Out of the Box Usage ..... 15
    - Object Reference..... 16
  - Applications ..... 16
    - Out of the Box Usage ..... 17
    - Object Reference..... 17
  - Deployment Units ..... 17
    - Out of the Box Usage ..... 18
    - Object Reference..... 18
  - Related Projects and Requests ..... 18
    - Out of the Box Usage ..... 18
    - Object Reference..... 19
  - Workflow Stages..... 20
    - Out of the Box Usage ..... 20
    - Object Reference..... 20
- Dashboard\_Schema\_DVM ..... 21

Introduction .....	22
Data Sources for Development Manager Metrics .....	22
Representing Data with Synonyms.....	22
Using This Content .....	22
Synonym Overview .....	22
Builds.....	23
Out of the Box Usage .....	23
Build Objects Reference.....	23
Change Requests .....	28
Out of the Box Usage .....	28
Object Reference.....	28
System Data .....	29
Out of the Box Usage .....	29
Object Reference.....	29
Development Packages .....	30
Out of the Box Usage .....	30
Object Reference.....	31
Projects .....	32
Out of the Box Usage .....	32
Object Reference.....	32
Test Data .....	33
Out of the Box Usage .....	33
Object Reference.....	33
Dashboard_Schema_RQM .....	34
Introduction .....	34
Data Sources for Requirements Manager Metrics .....	34
Representing Data with Synonyms.....	34
Using This Content .....	35
Synonym Overview .....	35
Requirement Approvals.....	35
Out of the Box Usage .....	35
Object Reference.....	36
System Data .....	37
Object Reference.....	37
Approval Ballots .....	38
Out of the Box Usage .....	38
Object Reference.....	38
Projects .....	40
Out of the Box Usage .....	40
Object Reference.....	40
Dashboard_Schema_ZMF .....	41
Introduction .....	41

---

---

Representing Data with Synonyms.....	42
Using This Content .....	42
Table Overview .....	42
List of All ZMF Objects .....	43
Object Reference.....	43
ZMF Servers.....	43
Object Reference.....	43
ZMF Dates .....	44
Object Reference.....	44
ZMF Subsystems.....	44
Object Reference.....	44
ZMF Apps .....	45
Object Reference.....	45
ZMF Packages .....	45
Object Reference.....	46

# Synonym Reference

---

Serena Dashboard is built from the ground up to aggregate and report on the most meaningful project and status level data from the Serena Orchestrated ALM solutions, including Serena Release Manager, Serena Development Manager, and Serena Requirements Manager. Serena Dashboard is powered by IBI WebFOCUS, a rich report building and generation system that can consume and display relevant data from any enterprise data source. WebFOCUS uses synonym files to represent imported data in a series of tables.

Serena Dashboard uses these synonyms to import data from the key Serena systems, including Serena Business Manager, Serena Dimensions CM, and Serena ChangeMan ZMF. The data is then available from these synonyms and their tables to the metrics that will make use of the data.

## Dashboard Metric Data Introduction

Overview

Understanding Synonyms [page 6]

Displaying Serena Dashboard Synonyms [page 7]

Using This Content [page 9]


### **Overview**

Serena Dashboard is built from the ground up to aggregate and report on the most meaningful project and status level data from the Serena Orchestrated ALM solutions, including Serena Release Manager, Serena Development Manager, and Serena Requirements Manager. Serena Dashboard is powered by IBI WebFOCUS, a rich report building and generation system that can consume and display relevant data from any enterprise data source. WebFOCUS uses synonym files to represent imported data in a series of tables.

Serena Dashboard uses these synonyms to import data from the key Serena systems, including Serena Business Manager and Serena Dimensions CM. The data is then available from these synonyms and their tables to the metrics that will make use of the data.

### **Understanding Synonyms**

Serena Dashboard provides a set of pre-configured master files that are used within WebFOCUS to build and display metrics. These master files store all of the data about the synonyms and tables that represent the actual data from the source. In its simplest form, think of a WebFOCUS synonym as depicted below.



The master files in WebFOCUS define a synonym that maps to the source data and is refreshed with the latest data at run time. When you display a metric in Serena Dashboard, WebFOCUS queries the data source and returns the current data to the synonym, which is then rendered into the metric.


In order to build new metrics in WebFOCUS, you can take advantage of the existing synonyms that are provided out-of-the-box with Serena Dashboard, or consult the IBI WebFOCUS documentation to learn how to build your own. This document describes the tables, columns and other data structures that are mapped from SBM, Dimensions CM, and other systems into the out-of-box synonym tables; you can use it to find and understand what columns to pull into your own, custom metrics.

## ***Displaying Serena Dashboard Synonyms***


Once you have completed installation of Serena Dashboard as documented in the Serena Dashboard Installation and Configuration Guide, you can open any of the master files provided with Serena Dashboard from WebFOCUS Developer Studio. The master files (.mas) store the synonym and table definitions, mapping data from columns in the data source tables to fields in the synonym tables.

To display and work with master files:

1. Open WebFOCUS Developer Studio.
2. In the Explorer view, under WebFOCUS Environments, expand the Dashboard environment (or localhost, however it is defined), expand EDASERVE.
3. From here, you can open the \Applications folder and see all of the files for specific WebFOCUS applications. For example, under \developmentmanagerdashboard, you see all of the master files for the Development Manager metrics under the Master Files folder.



- Each of the .mas / .acx file-pairs in this folder corresponds to a synonym, and stores the table definitions for that synonym. Double-click any of the .mas files to view the tables included in the synonym. For example, double-click ALMBaselineData to display the contents of the ALMBaselineData synonym.
- From the open synonym file, click the Modeling tab to see the representations of tables.



- This synonym includes two tables that map to data from the Development Packages process app in Serena Development Manager.

In this way, you can see for yourself the synonyms included with Serena Dashboard and review the data that each synonym can provide. This document provides a thorough overview of this data, however it does not list every column in every table; you may find that by exploring the synonyms directly you can find everything you need to build new metrics.



## **Using This Content**

This content provides you with an overview of the data provided to you via the tables defined in the out-of-box Serena Dashboard synonyms. You can read through the table and field descriptions to determine which data you need, and then open the synonyms directly in WebFOCUS Developer Studio to start working directly with the synonyms (see [Displaying Serena Dashboard Synonyms](#) [page 7]). This document provides shortcuts; you can scan tables and column names to find the data you need, then go to work building and customizing metrics in WebFOCUS Developer Studio.

# **Release Manager Metric Data Reference**

[Introduction](#) [page 9]

[Synonym Overview](#) [page 9]

[Release Trains](#) [page 10]

[Change Requests](#) [page 28]

[System Data](#) [page 12]

[Deployment Tasks](#) [page 14]

[Releases](#) [page 15]

[Applications](#) [page 16]

[Deployment Units](#) [page 17]

[Related Projects and Requests](#) [page 18]

[Workflow Stages](#) [page 20]

## **Introduction**

Review these topics before you get started learning about the Release Manager schema used by Serena Dashboard.

### **Data Sources for Release Manager Metrics**

Data for metrics on Serena Development Manager may come from multiple sources, including:

- Serena Business Manager
- Serena Dimensions CM

### **Representing Data with Synonyms**


This data is aggregated into tables within several synonyms in WebFOCUS Developer Studio that the metrics can draw from as needed. These synonyms are collections of tables that represent data as it is stored in the database tables in Business Manager, Dimensions CM, and other data sources. All of the out-of-the-box metrics included with Serena Dashboard draw data from these synonyms. By using these synonyms, you do not need to interact directly with the databases for the data sources; the synonyms do the work of mapping metrics to the source data without requiring advanced knowledge of the source database schemas. For more information, see [Understanding Synonyms](#) [page 6].

### **Using This Content**

To build your own metrics on Release Manager data, you can use the tables in these synonyms as well. This content is organized logically according to object type.

## **Synonym Overview**

The following diagram illustrates the Release Manager object data that is available to you via the out-of-box Serena Dashboard synonyms.



By opening and displaying the WebFOCUS synonyms directly, you can review all of the many fields available to you as you build new metrics using the out-of-the-box Serena Dashboard synonyms. For more on working directly with Serena Dashboard synonyms, see [Displaying Serena Dashboard Synonyms](#) [page 7].

## Release Trains

Data on release trains is stored in the URM\_RELEASE\_TRAIN table, which is used by several synonyms that provide project data to various metrics.

### Out-of-Box Usage

- The Compare Release Trains metric uses the RLMReleaseTrainData synonym to map data from the URM\_RELEASE\_TRAIN table to release data from other tables in the Release Manager synonyms. This metric compares the status and stage of multiple release trains.
- The Application Release Rates and Application Release Installation metrics use the RLMApplicationReleaseData synonym to map data from the URM\_RELEASE\_TRAIN table to deployment, request, application, and package data from other tables in the Release Manager synonyms. These metrics display application release rates and current status of installation steps.
- The Deployment Metrics metric uses the RLMDeploymentData synonym to map data from the URM\_RELEASE\_TRAIN table to deployment data. This metric displays the status of deployment activities by application and release train.

### Object Reference

There is one table, the URM\_RELEASE\_TRAIN table, that stores the release train data.

## URM\_RELEASE\_TRAIN

### Description

The URM\_RELEASE\_TRAIN table retrieves data from Serena Business Manager on release trains in the system. The data includes the primary ID, the Release Control project to which it is associated, the type of release, and the stage that the release train is currently in.

### Source

SBM schema.

### Fields

- `TS_ID`  
Primary key. Release train ID.
- `TS_PROJECTID`  
Project ID.
- `TS_RELEASE_TYPE`  
The type of release train. This may be major, minor, or emergency.
- `TS_STATE`  
The stage that the release train is currently in.
- `TS_APPLICATION_RELEASE`  
Associated application release.

## Release Packages

Data on release packages is stored in the `USR_RELEASE_PACKAGE` table, which is used by the `RLMApplicationReleaseData` and `RLMDeploymentPackHistory` synonyms. Specific information about the package states and transitions are stored in the `TS_CHANGEACTIONS`, `TS_TRANSITIONS`, `TS_STATES_PRIORSTATES`, and `TS_STATES_NEWSTATES` tables.

### Example Out-of-Box Usage

- The Application Release Rates and Application Release Installation metrics use the `RLMApplicationReleaseData` synonym to map data from the `USR_RELEASE_PACKAGE` table to release train, request and application data from other tables in the Release Manager synonyms. These metrics display application release rates and current status of installation steps.
- The Break/fix metric uses the `RLMDeploymentPackHistory` synonym to pull data about packages, including the break / fix information for each stage in a package.

### Object Reference

## USR\_RELEASE\_PACKAGE

### Description

The `USR_RELEASE_PACKAGE` table retrieves data on release packages stored in SBM. This data includes change requests and deployment units associated with the package, type, and other relationships.

## Source

SBM schema.

## Fields

- `TS_ID`  
Package ID.
- `TS_STATE`  
Release state that the package is currently in.
- `TS_RELEASE_REQUEST`  
ID of the associated release request.
- `TS_DEPLOYABLE_UNITS`  
Associated deployment units.
- `TS_RELATED_DCR_PROJECT`  
Project from which deployment change requests are retrieved.
- `TS_RELATED_DU_PROJECTS`  
Project from which deployment units are retrieved.
- `TS_ISSUETYPE`  
The type of release package, such as Dependent or Independent.
- `TS_VAULT_TYPE`  
The type of release vault.
- `TS_DEPLOY_STATE`
- `TS_DISPLAY_UNIT_PROJECTS`
- `TS_RELATED_PROJECTS`  
IDs of related projects from providers.
- `TS_DEPLOYMENT_TASKS`  
Associated deployment tasks.
- `TS_APPLICATION_RELEASE`  
Associated application release.
- `TS_DISPLAY_REQUEST_PROJECTS`
- `TS_MESSAGE_LOG`

## System Data

System data tables provide unique identifiers for a variety of object types. These tables are used by various synonyms to supply the identifiers for these objects to metrics.

## Object Reference

You can use the columns in the following tables to supply IDs to various objects in your own metrics.

---

## TS\_PROJECTS

### Description

Provides IDs for projects from providers. The `USR_APPLICATION_RELEASE` and `URM_RELEASE_TRAIN` tables refer to it.

### Source

SBM schema.

### Fields

- `TS_ID`  
Project ID.

## TS\_SELECTIONS

### Description

Provides IDs for various objects. In the Release Manager tables, `TS_SELECTIONS` provides IDs for release types to the `USR_APPLICATION_RELEASE` and `URM_RELEASE_TRAIN` tables.

### Source

SBM schema.

### Columns

- `TS_ID`  
Object ID.

## TS\_STATES

### Description

Provides IDs for workflow states. In the Release Manager tables, `TS_STATES` provides IDs for states to the `USR_APPLICATION_RELEASE` and `URM_RELEASE_TRAIN` tables.

### Source

SBM schema.

### Fields

- `TS_ID`  
State ID.

- TS\_NAME  
State name.
- TS\_STATUS
- TS\_OPENCLOSED

## **TS\_CHANGEACTIONS**

### **Source**

SBM schema.

### **Columns**

- TS\_ID  
Primary key. Change action ID.
- TS\_ACTION  
The action.
- TS\_ITEMID
- TS\_TABLEID
- TS\_TIME
- TS\_USERID

## ***Deployment Tasks***

Data on deployment tasks - including associated packages, tasks, requests, and applications - is stored in the `USR_DEPLOYMENT` table, which is used by the `RLMDeploymentData` and `RLMApplicationReleaseData` synonyms.

### **Out-of-Box Usage**

- The Deployment Metrics metric uses the `RLMDeploymentData` synonym to map data from the `USR_DEPLOYMENT` table to release train data. This metric displays the status of deployment activities by application and release train.
- The Application Release Rates and Application Release Installation metrics use the `RLMApplicationReleaseData` synonym to map data from the `USR_DEPLOYMENT` table to release train, request, application, and package data from other tables in the Release Manager synonyms. These metrics display application release rates and current status of installation steps.

### **Object Reference**

## **USR\_DEPLOYMENT**

### **Description**

Provides data about deployment activities as a whole; each record in this table includes information on associated release packages, requests, deployment units, stage in the deployment lifecycle, the type of deployment activity, the state of the associated deployment task, etc.

**Source**

SBM schema.

**Fields**

- `TS_ID`  
Primary key. Deployment ID.
- `TS_TASK_STATE`  
Current state of the deployment task.
- `TS_STATE`
- `TS_RELEASE_PACKAGES`  
IDs of associated release packages, from the `USR_RELEASE_PACKAGE` table.
- `TS_APPLICATION`  
Associated application, from the `USR_RELATED_DEPLOY_UNIT` table.
- `TS_RELEASE_REQUEST`  
Associated request for a release, from the `USR_RELATED_REQUESTS` table.
- `TS_RELATED_DEPLOY_UNIT`  
Associated deployment unit from the `USR_RELATED_DEPLOY_UNIT` table.
- `STAGE`  
Current release stage, from the `USR_RELEASETYPE_STAGE` table.
- `TS_AUTOMATION_TYPE`  
Automation type.
- `TS_DEPLOYMENT_TYPE`  
Type of deployment task: manual, approval, vault, or automation.
- `TS_TASK_STATES`  
States in the deployment task.
- `TS_RELEASE_ENGINEER`  
Primary owner of the deployment process.
- `TS_TEMPLATE`  
The deployment process template.
- `TS_VAULT_TYPE`  
Type of release vault, such as CM or ZMF.

**Releases**

Data on application releases is stored in the `USR_APPLICATION_RELEASE` table, which is used by several synonyms that provide project data to various metrics.

**Out-of-Box Usage**

- The Projects List metric uses the `RLMApplicationData` synonym to map application data from the `USR_APPLICATION` table to release data from the `USR_APPLICATION_RELEASE` table. This metric displays a list of applications as a project list.
- The Application Release Rates and Application Release Installation metrics use the `RLMApplicationReleaseData` synonym to map data from the `USR_APPLICATION_RELEASE` table to release train, deployment, request, application, and package data from other tables in the

Release Manager synonyms. These metrics display application release rates and current status of installation steps.

- The Deployment Metrics metric uses the RLMDeploymentData synonym to map data from the `USR_APPLICATION_RELEASE` table to release train and deployment data from other tables in the Release Manager synonyms. This metric displays the status of deployment activities by application and release train.
- The Compare Release Trains metric uses the RLMReleaseTrainData synonym to map data from the `USR_APPLICATION_RELEASE` table to release train and application data from other tables in the Release Manager synonyms. This metric compares the status and stage of multiple release trains.

## Object Reference

### USR\_APPLICATION\_RELEASE

#### Description

Provides data about application releases.

#### Source

SBM schema.

#### Fields

- `TS_ID`  
Primary key. ID of the release.
- `TS_UUID`
- `TS_ISSUETYPE`  
Type of associated request.
- `TS_ISSUEID`  
ID of associated request.
- `TS_TITLE`  
Application release name.
- `TS_APPLICATION`  
ID of the application.
- `TS_RELEASE_TRAIN`  
ID of the release train.
- `TS_DESCRIPTION`  
Description of the application release.
- `TS_PROJECTID`

## Applications

Data on applications is stored in the `USR_APPLICATION` table, which is used by several synonyms that provide application data to various metrics.



## Out-of-Box Usage

- The Projects List metric uses the RLMApplicationData synonym to map application data from the `USR_APPLICATION` table to release data from the `USR_APPLICATION_RELEASE` table. This metric displays a list of applications as a project list.
- The Application Release Rates and Application Release Installation metrics use the RLMApplicationReleaseData synonym to map data from the `USR_APPLICATION` table to release, release train, deployment, request, and package data from other tables in the Release Manager synonyms. These metrics display application release rates and current status of installation steps.
- The Deployment Metrics metric uses the RLMDeploymentData synonym to map data from the `USR_APPLICATION` table to release train and deployment data from other tables in the Release Manager synonyms. This metric displays the status of deployment activities by application and release train.
- The Compare Release Trains metric uses the RLMReleaseTrainData synonym to map data from the `USR_APPLICATION` table to release train and release data from other tables in the Release Manager synonyms. This metric compares the status and stage of multiple release trains.

## Object Reference

### USR\_APPLICATION

#### Description

Stores data about application definitions, which is in turn associated with releases.

#### Source

SBM schema.

#### Fields

- `TS_ID`  
Primary key. Application ID.
- `TS_UUID`
- `TS_TITLE`  
Name of the application.
- `TS_DESCRIPTION`  
Application description.
- `TS_LASTMODIFIEDDATE`  
Date when the application was last modified.
- `TS_DEPLOYMENT_PROCESS`
- `TS_LASTMODIFIER`  
ID of the user that last modified the application.

## Deployment Units

Data on deployment units is stored in the `USR_RELATED_DEPLOY_UNIT` table, which is used by the RLMApplicationReleaseData synonym.

### **Out-of-Box Usage**

- The Application Release Rates and Application Release Installation metrics use the RLMApplicationReleaseData synonym to map data from the `USR_RELATED_DEPLOY_UNIT` table to release, deployment, request, and package data from other tables in the Release Manager synonyms. These metrics display application release rates and current status of installation steps.

### **Object Reference**

## **USR\_RELATED\_DEPLOY\_UNIT**

### **Description**

Provides data on deployment units stored in SBM.

### **Source**

SBM schema.

### **Fields**

- `TS_ID`  
Primary key. Deploy unit ID.
- `TS_APPLICATION`  
Release application.
- `TS_RELATED_PROJECT`  
Project from the provider.
- `TS_RELATED_REQUEST`
- `TS_RELATED_DEPLOY`  
Related deployment task.
- `TS_TASK_STATE`  
State of the related task.
- `RS_RELATED_PACKAGE`  
Related deployment task.

### ***Related Projects and Requests***

Data on related projects and requests is provided by several tables. Request and project information originates with the registered change request and deployment provider.

### **Out-of-Box Usage**

- The Application Release Rates and Application Release Installation metrics use the RLMApplicationReleaseData synonym to map data on releases, release trains, deployment tasks, requests, and packages various Release Manager tables. These metrics display application release rates and current status of installation steps.

---

## Object Reference

### USR\_RELATED\_REQUESTS

#### Description

Provides information about related requests from the request provider.

#### Source

SBM schema.

#### Fields

- `TS_ID`  
Primary key. Request ID.
- `TS_UUID`
- `TS_TITLE`  
Name of the request.
- `TS_OWNER`  
User that owns the request.
- `TS_PACKAGE_ID`  
ID of the associated package.

### USR\_RELATED\_PROJECTS

#### Description

Provides information about projects from request and deployment unit providers.

#### Source

SBM schema.

#### Fields

- `TS_ID`  
Primary key. Request ID.
- `TS_PROJECT_TYPE`  
SBM or Dimensions CM.
- `TS_RELATED_PACKAGE`  
Associated package.

## **Workflow Stages**

Data on workflow stages and transitions is provided by several tables that are used by the RLMDeploymentPackHistory synonym. This includes the TS\_TRANSITIONS, TS\_STATES\_PRIORSTATES, TS\_STATES\_NEWSTATES, and TS\_TIMEINSTATE tables.

### **Out-of-Box Usage**

- The Break/fix metric uses the RLMDeploymentPackHistory synonym to pull data about packages, including the break / fix information for each stage in a package.

### **Object Reference**

#### **TS\_TIMEINSTATE**

##### **Description**

Amount of time spent in a particular state in the workflow.

##### **Source**

SBM schema.

##### **Fields**

- TS\_ID
- TS\_ENTERCHGACTIONID  
ID of the change action that moved the package from the previous state into the current state.
- TS\_EXITCHGACTIONID  
ID of the transition that moved the package into the next state.
- TS\_CALENDARID
- TS\_ELAPSEDTIME  
Measurement of elapsed time.

#### **TS\_STATES\_NEWSTATES**

##### **Source**

SBM schema.

##### **Fields**

- TS\_ID  
Primary key. State ID.
- TS\_NAME  
State name.
- TS\_STATUS  
State status.

- TS\_OPENCLOSED  
Whether the state is open or closed.

## TS\_STATES\_PRIORSTATES

### Source

SBM schema.

### Fields

- TS\_ID  
Primary key. State ID.
- TS\_NAME  
State name.
- TS\_STATUS  
State status.
- TS\_OPENCLOSED  
Whether the state is open or closed.

## TS\_TRANSITIONS

### Description

Workflow transitions.

### Source

SBM schema.

### Fields

- TS\_ID  
Primary key. State ID.
- TS\_NAME  
State name.
- TS\_PROJECTID
- TS\_OLDSTATEID

# Development Manager Metric Data Reference

Introduction [page 41]  
Synonym Overview [page 22]  
Builds [page 23]  
Change Requests [page 11]  
System Data [page 37]  
Development Packages [page 30]  
Projects [page 40]  
TS\_PROJECTID [page 33]

## ***Introduction***

Review these topics before you get started learning about the Development Manager schema used by Serena Dashboard.

### **Data Sources for Development Manager Metrics**

Data for metrics on Serena Development Manager may come from multiple sources, including:

- Serena Business Manager
- Serena Dimensions CM
- HP Quality Center

### **Representing Data with Synonyms**


This data is aggregated into tables within several synonyms in WebFOCUS Developer Studio that the metrics can draw from as needed. These synonyms are collections of tables that represent data as it is stored in the database tables in Business Manager, Dimensions CM, and other data sources. All of the out-of-the-box metrics included with Serena Dashboard draw data from these synonyms. By using these synonyms, you do not need to interact directly with the databases for the data sources; the synonyms do the work of mapping metrics to the source data without requiring advanced knowledge of the source database schemas. For more on this, please see Understanding Synonyms [page 6].

### **Using This Content**

To build your own metrics on Development Manager data, you can use the tables in these synonyms as well. This content is organized logically according to object type. For example, if you want to build a new metric that will report on change requests, refer to Change Requests [page 11] for details on the tables and fields that are available to you from the WebFOCUS synonyms.

## ***Synonym Overview***

The following diagram illustrates the set of tables related to Development Manager that are available to you via the out-of-box Serena Dashboard synonyms.



By opening and displaying the WebFOCUS synonyms directly, you can review all of the many fields available to you as you build new metrics using the out-of-the-box Serena Dashboard synonyms. For more on working directly with Serena Dashboard synonyms, see [Displaying Serena Dashboard Synonyms \[page 7\]](#).

## Builds

Data on build configurations from Dimensions CM are stored in the tables that belong to the ALMBuildData synonym. The ALMBuildData synonym stores data imported from Dimensions CM on build jobs, their status, development areas, and more.

### Out-of-Box Usage

In Serena Dashboard, the out-of-the-box metrics Build Details and Build Success Rate both pull in data from the ALMBuildData Synonym, in order to display information about build jobs that are managed in Dimensions CM and graphically indicate the overall rate of success of builds.

### Build Objects Reference

The ALMBuildData synonym contains the following tables. You can use the columns in the synonym tables to build your own metrics on build data.

## BLD\_BUILD\_JOB

### Description

Data on Dimensions CM build jobs. You can learn more about Dimensions CM published views in the [Serena Dimensions CM Reports Guide](#).

### Source

Dimensions CM schema.

### Fields

- `BUILD_JOB_ID`  
Primary key. Stores the ID of the Dimensions CM build job.
- `BUILD_ENV_ID`  
ID of the associated Dimensions CM build environment.
- `BUILD_AREA_ID`  
ID of the associated Dimensions CM build area.
- `BUILD_JOB_START_TIME`  
The start time for the build job.
- `BUILD_JOB_STOP_TIME`  
The stop time for the build job.
- `BUILD_JOB_USER`  
The user who created the build job.
- `BUILD_JOB_RESULT`  
The result of the build job.
- `BUILD_CONFIG_VERSION_ID`  
The ID of the version of the build configuration for the job.
- `CLEAN_BUILD`  
Whether the build job should clean the target directory before running.
- `SRC_BLINE_ID`  
The ID of the source baseline that the build job compiles.

### **BLD\_BUILD\_ENV**

#### Description

Data on Dimensions CM build environments.

#### Source

Dimensions CM schema.

#### Fields

- `BUILD_ENV_ID`  
Primary key. ID of the build environment.
- `BUILD_CONFIG_ID`  
ID of the build configuration for the environment.
- `BUILD_AREA_ID`  
ID of the build area.
- `BUILD_ENV_ASKPASSRUNTIME`  
Whether a password is required at runtime in order to run a build.



---

## **BLD\_BUILD\_CONFIG**

### **Description**

Data on Dimensions CM build configurations.

### **Source**

Dimensions CM schema.

### **Fields**

- `BUILD_CONFIG_ID`  
ID of the Dimensions CM build configuration.
- `PROJECT_ID`  
ID of the Dimensions CM build project.
- `PLATFORM_ID`  
ID of the Dimensions CM build platform.
- `BUILD_CONFIG_CURRENT_ID`  
ID of the current build configuration.

## **BLD\_BUILD\_CONFIG\_VERSION**

### **Description**

Data on versions of Dimensions CM build configurations.

### **Source**

Dimensions CM schema.

### **Fields**

- `BUILD_CONFIG_VERSION_ID`  
ID of the Dimensions CM build configuration version.
- `BUILD_CONFIG_ID`  
ID of the Dimensions CM configuration.
- `BUILD_CONFIG_VERSION_NUMBER`  
Dimensions CM build configuration version number.
- `BUILD_CONFIG_VERSION_DATE`  
Date that the build configuration version was created.

## **BLN\_CATALOGUE**

### **Description**

Data on Dimensions CM baselines.

### **Source**

Dimensions CM schema.

### **Fields**

- OBJ\_UID  
Baseline ID.
- OBJ\_SPEC\_UID  
Baseline specification ID.
- TYPE\_UID  
The type of baseline.

## **BLN\_SPEC\_CATALOGUE**

### **Source**

Dimensions CM schema.

- OBJ\_SPEC\_UID
- TYPE\_UID
- PRODUCT\_ID  
Product ID.
- OBJ\_ID

## **AREA\_CATALOGUE**

### **Description**

Data on Dimensions CM areas.

### **Source**

Dimensions CM schema.

---

**Fields**

- AREA\_UID  
Area UID.
- AREA\_ID  
Name of the area.
- NETWORKNODE\_UID  
ID of the network node.
- DIRECTORY  
Directory path to the area.

**WS\_CATALOGUE****Description**

Dimensions CM project / stream specification.

**Source**

Dimensions CM schema.

**Fields**

- OBJ\_UID  
Project / steam ID.
- OBJ\_SPEC\_UID  
Full specification of the project / steam.
- TYPE\_UID  
The type of project or stream.
- REVISION

**WS\_SPEC\_CATALOGUE****Source**

Dimensions CM schema.

**Fields**

- OBJ\_SPEC\_UID
- TYPE\_UID
- PRODUCT\_ID  
ID of the Dimensions CM product.
- OBJ\_ID

## Change Requests

Data on change request objects are stored in the `USR_DEVELOPMENT_CONTROL_CR` table. This table is used by the `ALMChangeRequestData` synonym, which stores data from Serena Business Manager on change requests and more.

### Out-of-Box Usage

- Using the `ALMChangeRequestData` synonym, the Project Defects Found metric maps data from the `USR_DEVELOPMENT_CONTRL_CR` table to data from the `USR_ALM_PROJECTS` table to display a bar graph of all defects in specific projects.
- Using the `ALMChangeRequestData` synonym, the Projects Defects by Month metric maps data from the `USR_DEVELOPMENT_CONTROL_CR` table to data from the `USR_ALM_PROJECTS` table to display an area graph of all defects found in specific projects on a month by month basis.
- Using the `ALMChangeRequestData` synonym, the Defects Escape Rate maps data from the `USR_DEVELOPMENT_CONTROL_CR` table to data from the `USR_ALM_PROJECTS` table to display a table of open and escaped defects for specific projects.

### Object Reference

#### USR\_DEVELOPMENT\_CONTROL\_CR

##### Description

This table stores data on development change requests managed by the Dev Change Requests process app.

##### Source

SBM schema.

##### Fields

- `TS_ID`  
Change Request ID.
- `TS_ASSOCIATED_BASELINE`  
Associated Dimensions CM baseline.
- `TS_ASSOCIATED_PROJECT`  
ID of the related project.
- `TS_PARENT_CR`  
If the request is a child request, stores the ID of the parent request.
- `TS_STATE`  
Current state of the request.
- `TS_LIST_OF_CHILD_TASKS`  
ID of tasks related to the request.
- `TS_LIST_OF_CHILD_CR`  
ID of any child requests, if the request is a parent request.
- `TS_ASSOCIATED_DEV_PACKAGES`  
Associated development packages.

- `TS_ISSUETYPE`  
Type of request, such as Defect.
- `TS_BUSINESS_PRIORITY`  
Business priority of the request.
- `TS_SEVERITY`  
Severity of the request.
- `TS_REASON_FOR_REJECTION`  
If the request was rejected, the reason provided for the rejection.
- `TS_QUALITY_ITEM_STATUS`  
Status of associated quality center items.
- `CM Projects`  
Associated Dimensions CM projects.
- `CM Products`  
Associated Dimensions CM products.
- `TS_PROJECTID`  
ID of the associated ALM project.

## **System Data**

System data tables provide unique identifiers for a variety of object types. These tables are used by various synonyms to supply the identifiers for these objects to metrics.

### **Out-of-Box Usage**

Using the `ALMChangeRequestData` synonym, the Project Defects Found, Project Defects by Month, and Defects Escape Rate metrics map IDs from the system tables to various objects.

### **Object Reference**

The following topics describe the system data tables.

## **TS\_STATES**

### **Description**

Data about workflow states.

### **Source**

SBM schema.

### **Fields**

- `TS_ID`  
State ID.
- `TS_NAME`  
State name.

## TS\_SELECTIONS

### Description

Provides IDs for various objects.

### Source

SBM schema.

### Fields

- TS\_ID  
Object ID.
- TS\_FLDID
- TS\_NAME  
Object name.
- TS\_NAMESPACEID

## TS\_USERS

### Description

Provides information on users.

### Source

SBM schema.

### Fields

- TS\_ID  
User IDs.

## ***Development Packages***

Data on development packages is stored in the USR\_DVM\_BASELINE table, which is used by the ALMBaselineData and ALMDvmPkgs synonyms.

Note that the synonym and table names refer to baselines, however this is not to be confused with Dimensions baselines. Baseline here refers to development packages.

### **Out-of-Box Usage**

- Using the ALMBaselineData synonym, the Project Baselines metric displays the success / failure rate for development packages in each project.
- Using the ALMDvmPkgs synonym, the Development Package per Project metric displays the total number of packages contained in each project, and at each state in the project.

---

## Object Reference

### USR\_DVM\_BASELINE

#### Description

This table stores data on development packages from the Dev Packages process app in Serena Development Manager.

#### Source

SBM schema.

#### Fields

- TS\_ID  
Development package ID.
- TS\_ASSOCIATED\_PROJECT  
Associated project from the ALM Projects process app.
- TS\_ORIGINATING\_BASELINE
- TS\_PREVIOUS\_BASELINE\_S\_PROJEC  
When creating a new revised baseline, this is the project or stream in Dimensions CM to which the original baseline belongs.
- TS\_PREVIOUS\_BASELINE\_S\_DEV\_PA  
When creating a new revised baseline, this is the development package to which the previous baseline is associated.
- TS\_PREVIOUS\_BASELINE  
When creating a revised baseline, the ID of the baseline to be revised.
- TS\_CURRENT\_BASELINE\_ITEM
- TS\_CURRENT\_BUILD\_STATUS  
Status of a current build task associated with the package.
- TS\_COLLECTION\_BUILD\_OUTPUTS
- TS\_AUTO\_REWISE\_BASELINE\_W
- TS\_ISSUETYPE
- TS\_CM Product  
Associated Dimensions CM product.
- TS\_CM Project  
Associated Dimensions CM project or stream.
- TS\_STATE  
Current workflow state of the package.
- TS\_PROJECTID

## Projects

Data on development projects is stored in the `USR_ALM_PROJECTS` table, which is used by several synonyms that provide project data to various metrics.

### Out-of-Box Usage

- The Project Change Request metric uses the `ALMProjectData` and `ALMChangeRequestData` synonyms to map project data from the `USR_ALM_PROJECTS` table to change request data from the `USR_DEVELOPMENT_CONTROL_CR` table. This metric displays the number of change requests in each stage in every project.
- The ALM Project Status metric uses the `ALMProjectData` synonym to pull data from the `USR_ALM_PROJECTS` table and display the current state, status, project manager, and last modified date of each project.
- The Development Package Iteration Count metric uses the `ALMProjectDataCount` synonym to map project data from the `USR_ALM_PROJECTS` table to development package data from the `USR_ALM_PROJECTS` table. This metric displays the number of attempts each package required before it was released. You can display a tabular version of this metric that indicates the project to which each package belongs.
- The Project Defects Found, Project Defects by Month, and Defects Escape Rate use the `ALMChangeRequestData` to map project data from the `USR_ALM_PROJECTS` table to change requests data from the `USR_DEVELOPMENT_CONTROL_CR` table. These metrics display defect counts against specific projects.
- The Development Package per Project metric uses the `ALMDvmPkgs` synonym to map data from the `USR_ALM_PROJECTS` table to data from the `USR_DVM_BASELINE` table. This metric displays the number of development packages in specific projects.

### Object Reference

## USR\_ALM\_PROJECTS

### Description

Stores data about projects from the ALM Projects process app.

### Source

SBM schema.

### Fields

- `TS_ID`
- `TS_ASSOCIATED_BASELINES`
- `TS_ISSUETYPE`  
Project type, such as Innovation or Operational.
- `TS_PROJECT_STATUS`  
Current project status.
- `TS_PROJECT_MANAGER`  
User who is the project manager.



- `TS_INCEPTION_ON_TIME`  
Whether the Inception phase is currently on-time.
- `TS_ELABORATION_ON_TIME`  
Whether the Elaboration phase is currently on-time.
- `TS_CONSTRUCTION_ON_TIME`  
Whether the Construction phase is currently on-time.
- `TS_TRANSITION_ON_TIME`  
Whether the Transition phase is currently on-time.
- `TS_PROJECTID`

## Test Data

Data on testing is stored in the `ALM_TEST_DATA` table, which is used by the `ALMTestData` synonym to provide project data to test metrics.

### Out-of-Box Usage

The Test Execution Status metric uses the `ALM_TEST_DATA` synonym to pull data from the `ALM_TEST_DATA` table and display status information on tests.

### Object Reference

## TC\_TESTCYCL

### Description

Data about test cycles from the test management system.

### Source

SBM schema.

### Fields

- `TC_TESTCYCLE_ID`  
Test cycle ID.
- `TC_CYCLE_ID`
- `TC_TEST_ID`  
Tests included in the test cycle.

## CYCLE

### Source

SBM schema.

### Fields

- `CY_CYCLE_ID`  
Cycle ID.
- `CY_CYCLE`  
Cycle name.
- `CY_OPEN_DATE`  
Date the cycle was started.

### CYCL\_FOLD

#### Source

SBM schema.

#### Fields

- `CF_ITEM_ID`
- `CF_ITEM_NAME`
- `CF_ITEM_PATH`

## Requirements Manager Metric Data Reference

Introduction [page 22]

Synonym Overview [page 35]

Requirement Approvals [page 35]

System Data [page 29]

Approval Ballots [page 38]

Projects [page 32]

### **Introduction**

Review these topics before you get started learning about the Requirements Manager schema used by Serena Dashboard.

#### **Data Sources for Requirements Manager Metrics**

Data for metrics on Serena Development Manager may come from multiple sources, including:

- Serena Business Manager
- Serena Dimensions RM

#### **Representing Data with Synonyms**

This data is aggregated into tables within several synonyms in WebFOCUS Developer Studio that the metrics can draw from as needed. These synonyms are collections of tables that represent data as it is stored in the database tables in Business Manager, Dimensions RM, and other data sources. All of the out-of-the-box metrics included with Serena Dashboard draw data from these synonyms. By using these synonyms, you do not need to interact directly with the databases for the data sources; the synonyms do the work of mapping metrics to the source data without requiring


advanced knowledge of the source database schemas. For more on this, please see Understanding Synonyms [page 6].

### Using This Content

To build your own metrics on Development Manager data, you can use the tables in these synonyms as well. This content is organized logically according to object type.

## Synonym Overview

The following diagram illustrates the set of tables related to Requirements Manager that are available to you via the out-of-box Serena Dashboard synonyms.



By opening and displaying the WebFOCUS synonyms directly, you can review all of the many fields available to you as you build new metrics using the out-of-the-box Serena Dashboard synonyms. For more on working directly with Serena Dashboard synonyms, see Displaying Serena Dashboard Synonyms [page 7].

## Requirement Approvals

Data on requirement approval objects are stored in the UCA\_CHANGE\_REQUEST table.

### Out-of-Box Usage

The UCA\_CHANGE\_REQUEST table provides information on requirement approvals to any metrics that reports on requirement approval status. This includes the Requirement Approval Status Distribution Across Projects and Average Requirement Approval Iteration Count Across Projects metrics.

## Object Reference

### UCA\_CHANGE\_REQUESTS

#### Description

The UCA\_CHANGE\_REQUESTS table stores data on requirement approvals in Serena Requirements Manager. All metrics that display information about requirement approvals draw data from this table.

#### Source

SBM

#### Fields

- TS\_ID  
Requirement approval ID.
- UUID  
Unique identifier for the requirement approval.
- TS\_TITLE  
Requirement approval title.
- TS\_DESCRIPTION  
Requirement approval description.
- TS\_STATE  
Current state of the approval.
- TS\_ASSOCIATED\_ISSUE  
ID of issue related to the approval.
- TS\_PROJECT\_ID  
ID of associated ALM project.
- TS\_CA\_ADDITIONAL\_NOTES  
Additional comments in the approval.
- TS\_REVIEWERS  
Requirement approval reviewers.
- TS\_CA\_REVIEWER
- TS\_LASTMODIFIEDDATE  
Date when the approval was last updated.
- TS\_ACTIVEINACTIVE  
Whether the approval is active or inactive.
- TS\_ISSUETYPE  
Type of approval.
- TS\_SUBMITTER  
Submitter of the approval.
- TS\_OWNER  
Owner of the approval.

- TS\_CLOSEDATE  
Close date for the approval.
- TS\_LASTMODIFIER  
User that last modified the approval.
- TS\_LASTSTATECHANGEDATE  
Date of the last change to a state.
- TS\_LASTSTATECHANGER  
User that last changed a state.
- TS\_SECONDARYOWNER  
Secondary owner of the approval.
- TS\_SUBMITDATE  
When the approval was submitted.
- TS\_CA\_REASON\_FOR\_CLOSE  
Reason for closing the approval.
- TS\_CA\_PARENT\_CHANGE\_REQUEST
- TS\_CA\_REVIEW\_SUBTASKS
- TS\_CS\_REVIEW\_STATUS

## **System Data**

System data tables provide unique identifiers for a variety of object types. These tables are used by various synonyms to supply the identifiers for these objects to metrics.

### **Object Reference**

The following topics describe the system data tables.

## **TS\_STATES**

### **Description**

Data about workflow states.

### **Source**

SBM schema.

### **Fields**

- TS\_ID  
State ID.
- TS\_NAME  
State name.

## **TS\_SELECTIONS**

### **Description**

Provides IDs for various objects.

### **Source**

SBM schema.

### **Fields**

- TS\_ID  
Object ID.
- TS\_FLDID
- TS\_NAME  
Object name.
- TS\_NAMESPACEID

## **TS\_USERS**

### **Description**

Provides information on users.

### **Source**

SBM schema.

### **Fields**

- TS\_ID  
User IDs.

## ***Approval Ballots***

Data on approval ballots (how users choose to vote on requirement approvals) is stored in the URA\_REQUIREMENTS\_APPROVALS table.

### **Out-of-Box Usage**

Data from the URA\_REQUIREMENTS\_APPROVALS table is used in metrics that display approval status, such as Requirement Approval Distribution for a Project, or Requirement Approval Distribution Across Projects.

### **Object Reference**

You can use the columns in this table to build your own metrics on development package data.

---

## URA\_REQUIREMENT\_APPROVALS

### Description

Stores data on approval ballots.

### Source

SBM

### Fields

- `TS_ID`  
Approval ballot ID.
- `TS_TITLE`  
Title of the approval ballot.
- `TS_REQUIREMENT_APPROVAL (id)`  
Identifier for the approval ballot.
- `TS_ALM_PROJECT`  
Associated ALM project.
- `TS_DVM_CHANGE_REQUEST`  
Associated change request from Development Manager.
- `TS_TARGET_DUE_DATE`  
Target due date for the ballot.
- `TS_DEV MANAGERS`  
Development managers assigned to the ballot.
- `TS_QA MANAGERS`  
QA managers assigned to the ballot.
- `TS_DISTRIBUTION_TASK_COMPLETE`
- `TS_REQUIREMENT_IDS`  
IDs of the requirements to be approved.
- `TS_REQUIREMENT_CLASS_NAMES`
- `TS_RM_SNAPSHOT_ID`  
ID of the snapshot in Dimensions RM.
- `TS_RM_SNAPSHOT_NAME`  
Name of the snapshot in Dimensions RM.
- `TS_RM_DOCUMENT_ID`  
ID of the requirements document in Dimensions RM.
- `TS_REVIEWERS_SUBMITTED`
- `TS_RM_SNAPSHOT_URL`  
URL to the Dimensions RM snapshot.
- `TS_RM_DOCUMENT_NAME`  
Name of the requirements document in Dimensions RM.

- `TS_RM_DOCUMENT_URL`  
URL to the requirements document in Dimensions RM.
- `TS_RM_SNAPSHOT_PREV_NAME`  
Previous name of the Dimensions RM snapshot.
- `TS_LASTMODIFIEDDATE`  
Last modified date of the approval ballot.
- `TS_LASTMODIFIER`  
User who last modified the approval ballot.
- `TS_LASTSTATECHANGER`  
User who last changed the state of the approval ballot.
- `TS_SUBMITTER`  
User who submitted the approval ballot.
- `TS_SUBMITDATE`  
Date when the approval ballot was submitted.
- `TS_CLOSEDATE`  
Date when the approval ballot was closed.
- `TS_STATE`  
Current state of the approval ballot.
- `TS_LASTSTATECHANGEDATE`  
Date when the state was last changed.
- `TS_ACTIVEINACTIVE`
- `TS_PROJECTID`  
ID of the ALM project (as stored in the `USR_ALM_PROJECTS` table).
- `TS_OWNER`  
Owner of the approval ballot.
- `TS_SECONDARYOWNER`  
Secondary owner of the approval ballot.
- `TS_ISSUETYPE`
- `TS_APPROVED_POLLS`

## **Projects**

Data on development projects is stored in the `USR_ALM_PROJECTS` table, which is used by several synonyms that provide project data to various metrics.

### **Out-of-Box Usage**

All out of box metrics that display information on a project by project basis, such as Requirements Approval Status Distribution Across Projects, pull data from the `USR_ALM_PROJECTS` table.

### **Object Reference**

#### **USR\_ALM\_PROJECTS**

##### **Description**

Stores data about projects from the ALM Projects process app.



---

**Source**

SBM schema.

**Fields**

- `TS_ID`  
Stores the project ID.
- `TS_ASSOCIATED_BASELINES`  
Associated baselines.
- `TS_ISSUETYPE`  
Project type, such as Innovation or Operational.
- `TS_PROJECT_STATUS`  
Current project status.
- `TS_PROJECT_MANAGER`  
User who is the project manager.
- `TS_INCEPTION_ON_TIME`  
Whether the Inception phase is currently on-time.
- `TS_ELABORATION_ON_TIME`  
Whether the Elaboration phase is currently on-time.
- `TS_CONSTRUCTION_ON_TIME`  
Whether the Construction phase is currently on-time.
- `TS_TRANSITION_ON_TIME`  
Whether the Transition phase is currently on-time.
- `TS_PROJECTID`  
Unique identifier for the project.

## ChangeMan ZMF Metric Data Reference

[Introduction \[page 34\]](#)

[Table Overview \[page 42\]](#)

[List of All ZMF Objects \[page 43\]](#)

[ZMF Servers \[page 43\]](#)

[ZMF Dates \[page 44\]](#)

[ZMF Subsystems \[page 44\]](#)

[ZMF Apps \[page 45\]](#)

[ZMF Packages \[page 45\]](#)

### **Introduction**

Review these topics before you get started learning about the ChangeMan ZMF data abstraction used by Serena Dashboard.

## Representing Data with Synonyms

ChangeMan ZMF data (on packages, servers, subsystems, etc.) is aggregated into tables within several synonyms in WebFOCUS Developer Studio. The Serena Dashboard metrics can then draw from these synonyms as needed. These synonyms are collections of tables that represent data as it is exposed via ChangeMan ZMF XML API. All of the out-of-the-box metrics included with Serena Dashboard draw data from these synonyms. By using these synonyms, you do not need to interact directly with ZMF; the synonyms do the work of mapping metrics to the source data without requiring advanced knowledge of the source database schemas. For more on this, please see Understanding Synonyms [page 6].


Uniquely to the ChangeMan ZMF metrics within Serena Dashboard, all of the data is stored in local XML files that are mapped, one to one, to the synonyms in WebFocus. These XML files can be refreshed as needed with new data from ChangeMan ZMF. In this way, the ZMF data is essentially cached in local files; The synonyms from which the Dashboard metrics are generated never directly interact with ChangeMan ZMF. This in turn improves performance. When you add ChangeMan ZMF data sources in Serena Dashboard, you determine how frequently the data should be refreshed.

### Using This Content

To build your own metrics on ChangeMan ZMF data, you can use the tables in these synonyms as well. This content is organized logically according to object type.

### Table Overview

The following diagram illustrates the set of tables related to ChangeMan ZMF that are available to you via the out-of-the-box Serena Dashboard synonyms.



By opening and displaying the WebFOCUS synonyms directly, you can review all of the many fields available to you as you build new metrics using the out-of-the-box Serena Dashboard synonyms. For more on working directly with Serena Dashboard synonyms, see Displaying Serena Dashboard Synonyms [page 7].

---

## List of All ZMF Objects

High level data on all ZMF objects including a count of servers, subsystems, applications, and packages is stored in the zmfalldata synonym. This synonym is used by the All Packages Average Lifecycle metrics.

### Object Reference

#### Description

The zmfalldata synonym stores summary data on ZMF objects across the implementation.

#### Source

ZMF

#### Fields

- `SERVERCOUNT`  
Number of ZMF servers in the implementation.
- `SUBSYSCOUNT`  
Number of ZMF sub-systems in the entire implementation.
- `APPCOUNT`  
Number of applications in the entire implementation.
- `PACKAGECOUNT`  
Number of packages in the implementation.

Many more fields are available as well, including `ICCREATEDACC`, `ICCREATEDCOUNT`, `ICFROZENACC`, `ICFROZENCOUNT`.

## ZMF Servers

High level data about ZMF servers is stored in the zmfserverlist synonym.

### Object Reference

#### Description

The zmfserverlist synonym contains data about specific ZMF servers.

#### Source

ZMF.

#### Fields

- `SUBSYSCOUNT`  
Number of subsystems on the server.
- `APPCOUNT`  
Number of applications on the server.

- PACKAGECOUNT  
Number of packages on the server.

Many more fields are available as well, including LCCREATEDACC, LCCREATEDCOUNT, LCCREATEDAVG, LCFROZENACC, LCFROZENCOUNT.

## **ZMF Dates**

Date information that can be mapped to ZMF objects is stored independently in the zmfdateslist synonym. This synonym is used by the All Packages Installed and All Packages Scheduled metrics.

### **Object Reference**

#### **Description**

The zmfdateslist synonym stores date information for ZMF objects.

#### **Source**

ZMF

#### **Fields**

- DATE  
A date, in the format YYYY-MM-DD.
- MONTH  
A month, in the format YYYY-DD.
- WEEK  
A week, in the format YYYY-MM-DD
- DAYS  
A week, in the format YYYY-MM-DD

## **ZMF Subsystems**

Data on ZMF Subsystems is stored in the zmfsubsystemslist synonym.

### **Object Reference**

#### **Description**

The zmfsubsystemslist synonym stores data about ZMF subsystems.

#### **Source**

ZMF

#### **Fields**

- SUBSYS  
Subsystem ID.

- APPCOUNT  
Number of applications in the sub system.
- PACKAGECOUNT  
Number of packages in the subsystem.

Other fields include LCCREATEDACC, LCCREATEDCOUNT, LCCREATEDAVG, LCFROZENACC, and more.

## **ZMF Apps**

Data on ZMF applications is stored in the zmfappslist synonym. This synonym is used by the All Applications by Instance, Application Average Lifecycle, and Instance Packages Average Lifecycle metrics.

### **Object Reference**

#### **Description**

The zmfappslist synonym stores data about ZMF applications.

#### **Source**

ZMF

#### **Fields**

- SUBSYS  
Subsystem ID.
- APPLNAME  
Application name.
- PACKAGECOUNT  
Number of packages in the application.

Other fields include LCCREATEDACC, LCCREATEDCOUNT, LCCREATEDAVG, LCFROZENACC, and more.

## **ZMF Packages**

Data on ZMF Subsystems is stored in a number of zmfpackageslist synonyms. Each synonym stores unique information on the packages. These synonyms include:

- zmfpackageslist: Stores all data about ZMF packages. This synonym is used by the All Packages by Application metric.
- zmfpackageslist1: Stores basic data about ZMF packages, and is used by several metrics that display basic package information. This synonym is used by the All Packages by Level, All Packages by Status, All Packages by Type, Application Packages by Status, Instance Packages by Application, and Status Packages by Instance metrics.
- zmfpackageslist2: stores promotion information about ZMF packages.
- zmfpackageslist3: stores installation date information about ZMF packages.
- zmfpackageslist4: stores expanded information about ZMF packages. This synonym is used by the Application Packages by Status and Application Packages metrics.

## Object Reference

### zmfpackageslist

#### Description

The zmfpackageslist synonym stores all data about ZMF packages.

#### Source

ZMF

#### Fields

- `PACKAGE`  
Name of the package.
- `SERVER`  
Server the package belongs to.
- `SUBSYS`  
Subsystem the package belongs to.
- `APPLNAME`  
Application the package belongs to.
- `REQUESTORNAME`  
User that requested the package.

### zmfpackageslist1

#### Description

The zmfpackageslist1 synonym Stores basic data about ZMF packages.

#### Source

SBM schema.

#### Fields

- `PACKAGE`  
Name of the package.
- `SERVER`  
Server the package belongs to.
- `SUBSYS`  
Subsystem the package belongs to.
- `APPLNAME`  
Application the package belongs to.

- `PACKAGESTATUS`  
Current status of the package.
- `PACKAGELEVEL`  
Package level.
- `PACKAGETYPE`  
Type of package.

## **zmfpackageslist2**

### **Description**

The `zmfpackageslist2` synonym stores promotion information about ZMF packages.

### **Source**

ZMF.

### **Fields**

- `PACKAGE`  
Name of the package.
- `SERVER`  
Server the package belongs to.
- `SUBSYS`  
Subsystem the package belongs to.
- `APPLNAME`  
Application the package belongs to.
- `PROMOTIONLEVEL`  
Promotion level of the package.
- `PROMOTER`  
User that promoted the package.
- `PROMOTIONDATE`  
Date that the package was promoted.

## **zmfpackageslist3**

### **Description**

The `zmfpackageslist3` synonym stores installation date information about ZMF packages.

### **Source**

SBM schema.

### Fields

- PACKAGE  
Name of the package.
- SERVER  
Server the package belongs to.
- SUBSYS  
Subsystem the package belongs to.
- APPLNAME  
Application the package belongs to.
- DATEINSTALLED  
Date the package was installed.
- MONTHINSTALLED  
Month that the package was installed.
- WEEKINSTALLED  
Week that the package was installed.

## zmfpackageslist4

### Description

The zmfpackageslist4 synonym stores expanded information about ZMF packages.

### Source

ZMF

### Fields

- PACKAGE  
Name of the package.
- SERVER  
Server the package belongs to.
- SUBSYS  
Subsystem the package belongs to.
- APPLNAME  
Application the package belongs to.
- DATEINSTALLED  
Date the package was installed.
- WORKCHANGEREQUEST  
Change request that lead to creation of the package.